

# Release Note

## SIP RAVA CLIENT V2.13E

<b>Document Name:</b>	Release Note																					
<b>Document ID:</b>	201412178ASI1																					
<b>Document Date:</b>	17. Dec. 2014																					
<b>Document Version:</b>	V1.00																					
<b>Firmware name:</b>	SIP RAVA CLIENT V2.13E																					
<b>FW Release Date:</b>	08. Sep. 2014																					
<b>Package Name:</b>	abcl_sip_v2.13e_20140908.zip																					
<b>Version Overview:</b>	<table><thead><tr><th>Type</th><th>File name</th><th>Version Date</th></tr></thead><tbody><tr><td>Firmware</td><td>abclw.rom</td><td>VA1.14_20140821</td></tr><tr><td>WEB UI</td><td>abclapp.cob</td><td>V02.07_20140820</td></tr><tr><td>FW Ext. 1</td><td>sg.bin</td><td>V10.05_20140618</td></tr><tr><td>FW Ext. 2</td><td>fs.bin</td><td>VA2.08_20140820</td></tr><tr><td>FW Ext. 3</td><td>bclio.bin</td><td>V02.02_20140808</td></tr><tr><td>Bootloader</td><td>exfull.rom</td><td>V99.26_20120223</td></tr></tbody></table>	Type	File name	Version Date	Firmware	abclw.rom	VA1.14_20140821	WEB UI	abclapp.cob	V02.07_20140820	FW Ext. 1	sg.bin	V10.05_20140618	FW Ext. 2	fs.bin	VA2.08_20140820	FW Ext. 3	bclio.bin	V02.02_20140808	Bootloader	exfull.rom	V99.26_20120223
Type	File name	Version Date																				
Firmware	abclw.rom	VA1.14_20140821																				
WEB UI	abclapp.cob	V02.07_20140820																				
FW Ext. 1	sg.bin	V10.05_20140618																				
FW Ext. 2	fs.bin	VA2.08_20140820																				
FW Ext. 3	bclio.bin	V02.02_20140808																				
Bootloader	exfull.rom	V99.26_20120223																				



# 1 Hardware Compatibility

---

This firmware is intended to run on the following devices:

- Annunicom 100/200 with IPAM 102

Note: While the firmware may run on any other Barix audio devices (e.g. Annunicom PS1, Annunicom PS16, etc), the complete functionality is not guaranteed in this case

## 2 New Features and Improvements

---

The following new features and improvements have been implemented in SIP-RAVA V2.13E compared to the previously released V2.13C :

- New Feature 120.08: Support up to 16 CIP peers in the IP table
- Bug 120.09: Improved the AEC performance by forcing the audio interface to work without reopening

## 3 Fixed Bugs

---

The following bugs have been fixed in SIP-RAVA V2.13E compared to the previously released V2.13C :

- Bug 120.10: Direct call fails with some IP addresses
- Bug: Fixed issue with empty IP and port when sending RINGING 180 in P2P mode
- Bug: Fixed to always reply to the configured CIP port instead of the detected remote port

## 4 Known Issues

---

The following issues have been detected when testing CIP enabled calls between the Barix SIP client and the CRESTRON TPMC-4SM-FD panel. For more details please refer to the provided test report

1. When a SIP call is initiated from the CRESTRON TPMC-4SM-FD panel, sometimes a second click is needed to send the SIP INVITE after fetching the necessary info by sending a 0xA6 CIP request message.
2. Limited UDP broadcast (sending to address 255.255.255.255) is not supported on Barix devices, so the CIP functionality has been implemented using local UDP broadcast.
3. When the “Beep on Call Answer” option is activated for Inbound and/or Outbound calls, the first 500ms audio sent by the remote party might be lost
4. AEC performance with the G.722 codec is not optimal, so the support for G.722 has been disabled in this release.
5. Starting from v2.13E of the SIP RAVA client the name of the BCL application has been changed from sip to sip\_rava. When upgrading the FW from versions prior to v2.13E the device might reboot automatically one more time after finishing the FW upgrade process in order to properly change the application name and avoid the step of manually reverting to factory defaults and reconfiguring again the device.

## 5 Supported CIP Functionality

---

The following CIP messages are supported in this version of the SIP RAVA client:

<i>Message type</i>	<i>RX</i>	<i>RX Action</i>	<i>TX</i>	<i>TX Action</i>
0x14	Yes	Reply with 0x15	No	
0x15	No		Yes	Sent in response of 0x14
0x16	Yes	Reply with 0x16	No	
0x17	No		Yes	Sent in response (unicast) of 0x16, and broadcasted 3 times at device boot
0x18	No		No	
0x19	No		No	
0xA6	Yes	Check if its ID is requested, and reply with 0xA7	Yes	Broadcast this query to get the IP to start a SIP call
0xA7	Yes	If in reply of its own 0xA6 request, then start SIP call	Yes	Sent in response of received 0xA6 query
0xA8	Yes	Check if its own SIP group is requested, and reply with 0xA9	Yes	Broadcast this query to collect info about all locations it is trying to reach
0xA9	Yes	Build IP table (max 8) of all locations, and start a group INVITE to all	Yes	Sent in response of received 0xA8 query

The following call scenarios are supported:

- Get CIP enabled SIP call from the Crestron TPMC-4SM-FD panel in P2P mode;
- Make outgoing CIP enabled SIP call to the Crestron TPMC-4SM-FD panel in P2P mode;
- Get CIP enabled SIP Group Page from the Crestron TPMC-4SM-FD panel in P2P mode
- Initiate multiple outgoing calls to maximum of 16 peers, and maintain only one active call (others are cancelled as soon as the first one picks up the call)
- IP table update supported only when sending SIP GROUP QUERY message

The following features are **NOT** supported:

- SIP Group paging initiated from the SIP client;
- LIGHT-N-POLL mode;

## 6 Release generating details<sup>1</sup>

---

### 6.1 CVS to GIT migration details

Starting from v2.13E the SIP-RAVA client has moved from the old CVS repository to the new GIT repository. In order to improve the SW maintenance, the SIP RAVA client as been migrated from the **crestron-sip-rava** branch to the repo **HEAD** as a **sip\_rava** ABCL application.

In this sense, the history starts from v2.13E onwards. To access previous application history, you need to checkout the code from the GIT repo using the old CVS branch tag **crestron-rava-sip**, then use the **gitk** tool to view older history

---

<sup>1</sup> This information is intended for BARIX developers only

## 6.2 GIT release tag

The barix and bcl repositories are tagged with the following tag:

```
abcl_sip_213e_20140908
```

## 6.3 Compile commands:

To compile this release, checkout the **barix** and **bcl** repositories with the tag mentioned above, then run the following command from the **barix** folder:

```
make ab_sip_rava
```

## 6.4 Regenerating the FW image

The source code of the SIP Client application is too big in size, and cannot fit into the COB file together with the tokenized BCL code. The generated release already has the source code stripped out of the FW image. However, if for some reason manual rebuild of the FW is needed, then the *applications.sh* script or the *applictns.bat* batch file has to be run with the **-no\_source** option to regenerate the applications.cob file:

```
./applications.sh -no_source
```

# 7 Legal Information

---

© 2014 Barix AG, Zurich, Switzerland.

All rights reserved.

All information is subject to change without notice.

All mentioned trademarks belong to their respective owners and are used for reference only.

Barix and SIP CLIENT are trademarks of Barix AG, Switzerland and are registered in certain countries.

**RAVA** is a trademark of Crestron Electronics, Inc.

For information about our devices and the latest version of this manual please visit

[www.barix.com](http://www.barix.com)

Barix AG  
Seefeldstrasse 303  
8008 Zürich  
SWITZERLAND

T +41 43 433 22 11  
F +41 44 274 28 49

www.barix.com  
sales@barix.com  
support@barix.com