

BARIX

THE VOICE OF SIMPLICITY

ANNUNCICOM 200 PSU



24VDC / 18W universal power supply for Annunicom 200. The power supply is delivered with adapters for EU, US, UK and Chinese plugs.

Technical Specifications

General characteristics

- Total output power: 18Watts
- Short circuit protection: No damage when output is shorted to GND and after short circuit, auto restart
- Overshoot / Undershoot: 24V \pm 10%

Input characteristics

- Input voltage rating: 100-240V AC
- Input frequency rating: 60/50Hz

Efficiency Information

- Efficiency complies CEC level V and ERP 2

Mechanical

- Weight 159,4g

Output characteristics

- Output voltage: 24V
- Max. load current: 750mA
- Min. load current: 0A
- Output voltage (load & no load): 24V \pm 5%
- Output ripple & noise: 280mV max.

Reliability

- MTBF: 20K hours min. @ full load at 25°C ambient temperature
- Altitude: Will operate properly at altitude between 0 to 10000ft

Environmental

Operating temperature

0 to +40°C

Storage temperature

-25°C to +85°C

Operating humidity

8% to 90%

Storage humidity

5% to 95%

Certifications/compliant with

Application safety standard: meet

- UL 60950, EN 60950, AS/NZS 60950, J 60950, GB 4943

EMI standard: meet

- UL FCC Part 15 Class B : 2008
- EN 55022 : 2006
- GB 9254-2008
- J 55022

Product Number 2011.5032

Barix AG – Seefeldstrasse 303 – CH-8008 Zurich – info@barix.com – www.barix.com
Phone: +41 43 43322 11 – Fax: +41 44 2742849

© Barix AG 2013, all rights reserved. All information is subject to change without notice.
All mentioned trademarks belong to their respective owners and are used for reference only. Product sheet V3.0

