

BARIX

Annunicom PS Touch

Desktop IP Intercom and paging master station with touch screen, PoE powered.



The Barix Paging Station Annunicom PS Touch is a universal, TCP/IP connected intercom station for use in IP Intercom, Paging and VoIP applications. The PS Touch directly connects to the network via a 10/100Mbps network connection, and is powered over the network interface (PoE, 802.3af standard).

The station can be used as a master station for IP based intercom and paging systems, which can be built without any central servers or PCs.

The PS Touch is equipped with a touch screen display, an XLR connected professional gooseneck microphone and a built-in speaker. Optional flash memory for stored messages and announcements is available.

Annunicom PS Touch is delivered with Barix Simple Paging Master station firmware or as an IC Paging talk station. Additional firmware support on request.

Applications

- Factory floors, corporate buildings
- Firefighter teams, hospitals, airports
- Schools, campuses, train stations

Features

- High audio quality
 - High contrast capacitive 10.1" touch screen
 - Robust metal case
 - Haptic mechanical talk button
 - Works with Barix Simple Paging or IC Paging solution
 - PoE powered
-

Technical Specifications

Power Supply Input

- Powered over the network interface (PoE, 802.3af standard)

1 Ethernet Interfaces

- RJ45 10/100 auto detect, IPv4, IPv6
- TCP/IP, RTP, UDP, ICMP, DHCP, SNMP

Audio Input

- XLR microphone connector with 13 Volt bias voltage

Audio output

- 5-Watt output speaker

Touch Screen

- 10.1" size
- Touch type: capacitive
- 1024x600 pixel resolution
- backlight LED >30,000 hours
- >1 million touches

Barix solution support

- Supports Barix Simple Paging
- IC Paging on request at order
- SIP on request

HW/SW environment

- Barix IPAM302
- Simple Paging firmware preinstalled

User Interface

- Web interface for control, status and configuration

Case

- Metal
- 350x250x150mm (13.8x9.8x5.9 inch)
- without microphone
- ~ 2500g

MTBF

- 30'000 hours

Warranty

- Two years

Environmental

Operating Environment

0 to +50°C / 32 to 122°F
0 - 70% relative humidity, non-condensing

Storage Conditions

-20 to +70°C / -4 to 158°F
0 - 70% relative humidity, non-condensing

Certifications

CE, RoHS, others in examination

Ordering Information

2020.9305 - Annunicom PS Touch SimplePaging
2020.9315 - Annunicom PS Touch IC-Paging

For commercial related questions (distributors, price list, business opportunities) please contact.

sales@barix.com

For technical inquiries (problem reports, request for documentation, etc.) please contact.

support@barix.com

Barix AG

Ringstrasse 15A, CH-8600 Dübendorf, www.barix.com
Phone: +41 43 43322 11



© Barix AG 2020, all rights reserved. All information is subject to change without notice.

All mentioned trademarks belong to their respective owners and are used for reference only. Product sheet V0.3
