

BARIX

BARIONET 1000

Universal, programmable I/O Device Server



Barionet 1100 is a device server, based on Linux/Lede/OpenWRT. The device features a wide range of interfaces such as two USB, WiFi, RS322 serial port, analog and digital I/Os, Relays and Dallas 1-wire support. It is IPv4 or IPv6 capable. Supporting SNMP, Modbus and universal ASCII protocols, the Barionet device can be easily integrated into 3rd party management systems. Barix Products are developed in Switzerland and manufactured in the EU.

Applications

- Automation engineering in buildings, public transport and network infra-structures
- Machine control
- Access control and security systems driving horns or lights
- Environmental monitoring at power stations, sluices, or in agriculture
- Contact closure monitoring
- Logging of temperature and humidity
- HVAC steering
- PV power management

Specifications

- Embedded Linux / Lede / OpenWRT
 - Programmable in C++, Lua or Python
 - IPv4 / IPv6 stack
 - One 10/100 Ethernet port
 - Wi-Fi 802.11 b/g/n, 2.4Ghz
 - 2 Relay outputs
 - 4 Digital Outputs
 - 4 Digital Inputs
 - 4 Universal Inputs (analog or digital)
 - RS232 Interface
 - 2 USB Host Interfaces
 - Interface for temperature sensor – Dallas 1-wire® 18DS20
 - Barionet DIN-Rail Case
 - Supply Voltage 9-30 VDC
-

Technical Specifications

Operation System

- Linux / Lede / OpenWRT

Network / WiFi Interfaces

- 1 x Ethernet (RJ45) Interface
- IPv4, IPv6 capable
- 10/100 fdx/hdx, auto negotiation
- WiFi 802.11 b/g/n, 2.4 GHz
- TCP/IP, UDP, ICMP, DHCP, CGI, HTTP, SNMP

I/O Interface

- 2 x Relay Outputs (30VDC, 5A)
- 4 x Digital Outputs (open-collector, 24VDC, 0.3A)
- 4 x Digital Inputs (0-15VDC) with conf. pullups
- 4 x Universal Inputs (Analog 0-15VDC 12bit or Digital 0-15VDC) with configurable pullups

Serial Interface

- 1 x RS-232 (DSub-9 male) Interface
- 600-115'200 baud rate, 7-8 bit, O/E/N Parity

USB Interface

- 2 x USB Host (Type A) Interface

Miscellaneous Interfaces

- Universal Dallas 1-Wire® Interface for external temperature sensors 18DS20 and other 1-Wire® equipment

CPUs / Memory

- MediaTek MT7620A, Qino Module
- 64MB SDRAM
- 16MB Flash

User Interface

- Web interface for control / configuration
- 11 x LED Status indicators

Power Requirements

- Single 9-30V DC supply voltage, 2.5 Watt

MTBF

- > 950'000h

Measurement

- 4.05" x 3.35" x 1.22" / 103mm x 85mm x 31mm

Weight

- 180g

Warranty

- Two years

Environmental

Operating Environment

-40°C to + 60° / -40 to 140°F environmental
0 - 70% relative humidity, non-condensing

Storage Conditions

0 to +70°C / 32 to 158°F
0 - 70% relative humidity, non-condensing

Certifications

RoHS, FCC (A&B), CE (A&B)

Ordering Information

2016_9187P_BARIONET 1000 NO PSU

For commercial related questions (distributors contacts, price list, business opportunities) please contact **sales@barix.com**

For technical inquiries (problem reports, request for documentation, etc.) please contact **support@barix.com**

Barix AG

Ringstrasse 15A, CH-8600 Dübendorf, info@barix.com, www.barix.com
Phone: +41 43 43322 11, Fax: +41 44 2742849



© Barix AG 2017, all rights reserved. All information is subject to change without notice.
All mentioned trademarks belong to their respective owners and are used for reference only. Product sheet V0.2
