


BARIX

THE VOICE OF SIMPLICITY

IP AUDIO MODULE 300

low cost version with limited feature set, one serial port, digital I/O, Decoding only, 3.3V supply



The Barix IP AUDIO MODULE 300 is a versatile network audio decoder module that plays AAC+, MP3, Ogg Vorbis, WMA, G.711 and PCM audio. It is easily incorporated into applications to play files and playlists from USB memory, PC or web server (http), or to stream from sources like Shoutcast, Icecast (Internet radio) or RTP servers.

Installation and configuration

Installing a device containing the IP AUDIO MODULE 300 is fast and simple: After power-up the module will either get an IP address automatically (BootP or DHCP), or will find one using the IPzator feature. The unique SonicIP feature then announces the IP address over the audio outputs! The module is easily configured and controlled by a standard web browser.

Firmware options

A) Exstreamer Standard firmware for jukebox and multizone applications, B) Exstreamer Streaming Client firmware for commercial streaming applications with AAC+, WMA, Ogg Vorbis and MP3 support, automatic failover (up to 3 URL's / playing from USB memory)

Applications IP Audio Module 300

- Playing audio from PC, jukebox applications, flash memory
- Multiroom or multizone distributed audio systems
- Commercial audio streaming applications (airports, hotels, etc.)
- Realtime audio bridging over IP (when used with the Instreamer)
- Paging and announcement applications
- Instore audio distribution (realtime) for retail, restaurants, franchises

and monitoring capabilities. C) ABCL development kit: a simple to use, powerful Basic dialect allows for custom application development (please see the ABCL programmers manual & technical doc.).

Application development and integration

The IP AUDIO MODULE 300 supports various control and communication modes. Software developers can easily write audio applications using one of the openly documented Ethernet (cgi, TCP, UDP) or serial interfaces (API).

Hardware integration and evaluation

For hardware integration a development specification with schematic, pinout and suggestions for the layout of a custom carrier PCB is available. For evaluation purposes, Barix recommends any Barix Exstreamer 1xx family device.

Other modules

While the Barix IP AUDIO MODULE 300 decodes only, the Barix IP AUDIO MODULE 102 can decode as well as encode, providing analog as well as digital audio interfaces.

Software IP Audio Module 300 available

- Decodes AAC+, MP3, OggVorbis, G.711 and PCM formats from network, local flash memory or local USB memory
 - 10/100 Mbit Ethernet connection
 - Controllable by web browser and API
 - Standard and fully programmable ABCL (Basic dialect) firmware versions available (OEM versions on request)
-

Technical Specifications

Audio Interfaces and Formats

- I2S bus (Inter-IC Sound), Analog stereo out 1.5Vpp,
- Volume, base and treble adjustable by application
- AAC+ (HE-AAC V2 incl SBR and PS, needs licensing
- by OEM), MP3 up to 320 kBit fixed & variable bit
- rates, Ogg Vorbis (floor 1), WMA, G.711 (uLaw /
- aLaw @ 8 to 48 kHz), PCM (16 bit @ 8 to 48 kHz)

Network Interface

- 10/100 Mbit Ethernet (Auto), TCP/IP, UDP, RTP, HTTP, DHCP, SNMP, AutoIP, SonicIP, IPzator, ES-100/SPKR (Ethersound)

Misc. Interfaces

- TTL Level UART 300..230'400 Baud
- Outputs for 2 dualcolor Ethernet status LEDs,
- 4 General Purpose I/Os, 1 input for reset button,
- 2 status LED outputs), USB1.1 interface for memory

CPU / Memory

- Integrated CPU / MAC / IO controller with on-chip 256 KB RAM, 2 KB EEPROM (configuration), 2 MB Flash memory (application and web server content)

Operating System

- Embedded, robust OS, IP stack with Multicast support

User / Application Interfaces

- Integrated web server (control/configuration),
- browser based, serial or Ethernet control API,
- programmable software environment

Power requirements

- Single 3.3 VDC, 1.6 Watt max.

Weight, dimensions

- 14 g approx.
- 2.2" x 1.3" x 0.39", 56 mm x 33 mm x 10 mm

MTBF

- Min. 950 000h acc. to MIL217F at 40°C

Environmental

Operating Environment

0 to +60°C / 32 to 140°F

Storage Conditions

0 to +85°C / 32 to 185°F,

both 0 - 70% relative humidity, non-condensing

Certifications/compliant WITH

RoHS compliant (lead free)

Ordering Information

2012.9122 IPAM 300

Sold in quantities of 10, 200 and 1000.

For commercial related questions (distributors contacts, price list, business opportunities) please contact **sales@barix.com**

For technical inquiries (problem reports, request for documentation, etc) please contact **support@barix.com**

Barix AG – Seefeldstrasse 303 – CH-8008 Zurich – info@barix.com – www.barix.com
Phone: +41 43 43322 11 – Fax: +41 44 2742849



© Barix AG 2015, all rights reserved. All information is subject to change without notice.
All mentioned trademarks belong to their respective owners and are used for reference only. Product sheet V3.0
