

BARIX

by digigram

X/LINK-ST

Stereo IP Audio Codec

SDHC card reader for backup playlists, and loading/saving the codec configuration

Low consumption, fanless, multi-format encoding and multi-protocol streaming

Easy and fast status monitoring: status LEDs, LCD display and keypad, vu-meters, headphones



2 analog I/O's and 1 stereo AES/EBU I/O

4 GPIO's for signalling of physical status

2 internal redundant PSUs for secure operation



Switchable hardware by-pass of audio inputs to outputs in case of power supply failure.

4 GPIO's for signalling of physical status

RS232 port for serial data signalling

4 network ports for full separation of IP traffic:
• AES67, RAVENNA, Livewire (LAN)

BARIX by digigram X/LINK-LE is a professional IP audio codec designed for the highest needs in terms of reliability and redundancy, delivering a stereo or two mono sources. It can be used in legacy analog or AES/EBU audio infrastructures, as well as in full-IP audio infrastructures (AES67, Ravenna, Livewire), making it a good investment for the migration to IP audio. X/LINK-ST is based on Fluid IP technology which offers redundant dual streaming and multiple redundancy for fail save connections. It is based on a powerful, low consumption, high redundant, fanless hardware platform.

Applications

- SSL, STL
- Hybrid environment with analog, digital and IP infrastructure
- Installations with planned path to IP audio
- Easy integration into existing SNMP based supervisors (SET, GET, Traps)
- Designed for audio service continuity and failsafe operation.

Features

- Adapted to your current legacy audio infrastructure & to your future full-IP audio infrastructure
- Simultaneous delivery of your audio program to transmitter sites, WEB radio CDNs, DVB multiplexers & other studios, in multiple audio formats
- Designed for audio service continuity and failsafe operation
- Easy integration into existing SNMP based supervisors (SET, GET, Traps)
- Ongoing product support with flexible options

Technical Specifications

Power Supply

- 2x internal redundant PSUs 100-250VAC, 15W

Network

- 4 networks ports 1x 100 Mbps, 3x Gbps on RJ-45 ports
- 2 balanced analog I/Os & 1 stereo AES/EBU I/Os with hardware sample rate converters
- 8 GPI/8 GPO on Sub-D25 connector
- One RS232 port for serial data tunneling
- Possibility to separate the network traffics (WAN, LAN, management) via the 4 networks ports
- VLANs, QoS (VLAN Tagging, DSCP)
- IGMPv2 and v3

Audio formats

- Each input and output can be analog, AES/EBU, AES67, or RAVENNA or Livewire
- Multi-format encoding and multi-protocol streaming of the audio sources
- PCM linear 16/20/24 bits, ITU G.711/722, ISO MPEG-1/2 Layer II, Layer III, MPEG-4 AAC-LC, AAC-LD, HE-AACv2, HE-AACv1, AAC-ELD, Opus
- Streaming protocol: RTP/UDP with or without MPEG-TS encapsulation (SPTS, MPTS), Icecast/Shoutcast
- Unicast, multi-unicast, multicast, multi-multicast addressing
- Dual port redundant streaming on WAN, with time diversity up to 3 seconds
- Selectable FECs for ACIP streams (from +15% to +100% IP bandwidth)
- Pro-MPEG CoP #3 FEC for MPEG-TS
- Real-time metrics on network path quality for the primary stream as well as for the FEC/redundant stream
- AES transparent transport
- Optional transcoding (ACIP, HTTP, MPEG-TS)

Input/Output

- 4 network ports for full separation of IP traffics:
- AES67, RAVENNA, Livewire (LAN)
- Redundant dual streaming (WAN)
- Remote management (LAN / WAN)

Audio Management

- Silence detection on the audio inputs and on the received IP audio streams
- Auxiliary data tunneling (serial Data and GPIs, physical or virtual, RDS-UCEP)
- Metadata insertion to HTTP streams (static, dynamic)
- Clock synchronization: internal, PTP, Livewire clock
- Three decoding priorities per output program, with choice of the audio source on each priority: IP stream (RTP, UDP, HTTP), local files & playlists on SDHC card, audio inputs
- Automatic switching between encoding priorities according to adjustable criteria
- Configuration and monitoring via intuitive WEB GUI n via SNMP
- Alarm via SNMP Traps
- Hardware by-pass of the first stereo input to first the stereo output (analog and AES/EBU)
- Optional: Audio synchronization of decoders based on NTP, or PTP

User Interface

- Web interface for control, status and configuration
- LEDs for status and VU meter, HW reset button

Case & Weight

- Height: 1U
- Width: 19" / Length: ~10,63" (270mm)
- Weight: 6,85 lbs (~3.1kg)

Environmental

Operating Environment

- 32° to 122°F (0 to +50°C)
- 0 - 95% relative humidity, non-condensing

Storage Conditions

- -23° to 158°F (-5 to +70°C)
- 0 - 95% relative humidity, non-condensing

Certifications

FCC, EMC, IEC, EN, RoHS

Ordering Information

2019.7001 BARIX X/LINK-ST

For commercial related questions (distributors contacts, price list, business opportunities) please contact: sales@barix.com

For technical inquiries (problem reports, request for documentation, etc.) please contact support@barix.com

Phone: +41 43 43322 11, Fax: +41 44 2742849



© Barix AG 2019, all rights reserved. All information is subject to change without notice.

All mentioned trademarks belong to their respective owners and are used for reference only. Product sheet V1.0