

# **RELEASE NOTE**

### **Streaming Client V3.21**

Firmware name:	Streaming Client V3.21			
Released:	24 <sup>th</sup> August 2021			
Package name:	streaming_client_v0321_20210824.zip			
Version overview:	Type	File Name	Version/Date	
	Firmware	stream.rom	V03.21 20210824	
	WEB UI	streamapp.cob	V04.18_20210824	
	FW Ext. 1	sg.bin	V10.18_20171019	
	FW Ext. 2	fs.bin	V02.08_20140820	
	FW Ext. 3	bclio.bin	V02.06_20151028	
	Update mod.	rupdate.bin	V01.01_20141124	
	Bootloader	unifull.spb	V99.28_20160624	

### 1 Hardware Compatibility

This firmware is intended to run on the following devices:

- Exstreamer 100, 105, 110, 120, 200, 205, 500, 1000
- Exstreamer P5
- IPAM 100, 102, 300

**Note**: The firmware can run on any other Barix audio devices (e.g. Annuncicom, Exstreamer Digital), however the functionality is not guaranteed.

AAC+ decoding is available only on IPAM 300, IPAM 302 and IPAM 102 based hardware (Exstreamer 100, 105, 110, 120, 200 and 205 labelled "AAC+ capable").

Please note that the Remote Firmware Update feature is supported only on devices with 2MB of Flash memory.

# 2 Bugs Fixed In This Version

The following bugs have been fixed in the Streaming Client V3.21 since the last officially released version V3.20.

• Fixed broken image generation script for 64 bit MacOS

### 3 New Features in This Version

The following new features have been added in the Streaming Client V3.21 since the last officially released version V3.20.

• #SC-305: Add support for the new IR remote control

### 4 Known Bugs/Restrictions

#### 4.1 Contact closures in RTP

I/O over RTP (contact closures sent by the Instreamer) are not fully in sync with audio, the audio buffer is not respected.

#### 4.2 Volume Source Control

The Volume Source Control panel (VSC) uses a serial polling protocol to transfer data between the Barix unit and the VSC. This protocol causes additional load, which on some devices may cause audio dropouts while playing very high bitrate audio.

### 4.3 Relay On when playing from USB

When the relay function is set to "Streaming and Priority", and the USB playback is set as the main URL, the relay may not trigger back to "ON" when the priority message ends

### 5 References

	Document
[1]	Streaming Client Technical Documentation 3.17

## 6 Legal Information

© 2021 Barix AG, Zurich, Switzerland.

All rights reserved.

All information is subject to change without notice.

All mentioned trademarks belong to their respective owners and are used for reference only.

Barix and Streaming Client are trademarks of Barix AG, Switzerland and are registered in certain countries.

For information about our devices and the latest version of this manual please visit www.barix.com.

Barix AG Limmatstrasse 21 8005 Zürich SWITZERLAND

T +41 43 433 22 11 F +41 44 274 28 49

www.barix.com sales@barix.com support@barix.com